



图号: U

	1	2	3	4																																																																																		
A	<div>未注公差尺寸加工允许偏差表</div> <div><div>(H14,h14,±t2/2或±IT14/2)</div><div>未注公差尺寸加工允许的偏差-线性尺寸</div><table><thead><tr><th>尺寸(mm)</th><th>轴公差</th><th>孔公差</th><th>其余尺寸公差</th></tr></thead><tbody><tr><td>≥0.5≥3</td><td>(-0.2,0)</td><td>(0,+0.2)</td><td>(-0.1,+0.1)</td></tr><tr><td>>3≥6</td><td>(-0.2,0)</td><td>(0,+0.2)</td><td>(-0.1,+0.1)</td></tr><tr><td>>6≥30</td><td>(-0.4,0)</td><td>(0,+0.4)</td><td>(-0.2,+0.2)</td></tr><tr><td>>30≥120</td><td>(-0.6,0)</td><td>(0,+0.6)</td><td>(-0.3,+0.3)</td></tr><tr><td>>120≥400</td><td>(-1,0)</td><td>(0,+1)</td><td>(-0.5,+0.5)</td></tr><tr><td>>400≥1000</td><td>(-1.6,0)</td><td>(0,+1.6)</td><td>(-0.8,+0.8)</td></tr><tr><td>>1000≥2000</td><td>(-2.4,0)</td><td>(0,+2.4)</td><td>(-1.2,+1.2)</td></tr><tr><td>>2000≥4000</td><td>(-4,0)</td><td>(0,+4)</td><td>(-2,+2)</td></tr><tr><td>>4000≥6000</td><td>(-6,0)</td><td>(0,+6)</td><td>(-3,+3)</td></tr><tr><td>>6000≥8000</td><td>(-10,0)</td><td>(0,+10)</td><td>(-5,+5)</td></tr><tr><td>>8000≥10000</td><td>(-16,0)</td><td>(0,+16)</td><td>(-8,+8)</td></tr></tbody></table></div> <div><div>(H14,h14,±t2/2或±IT14/2)</div><div>未注公差尺寸加工允许的偏差-倒角半径和倒角高度</div><table><thead><tr><th>尺寸(mm)</th><th>公差</th></tr></thead><tbody><tr><td>≥0.5≥3</td><td>(±0.2)</td></tr><tr><td>>3≥6</td><td>(±0.5)</td></tr><tr><td>>6</td><td>(±1)</td></tr></tbody></table></div> <div><div>(H14,h14,±t2/2或±IT14/2)</div><div>未注公差尺寸加工允许的偏差-角度</div><table><thead><tr><th>长度分段尺寸(mm)</th><th>公差</th></tr></thead><tbody><tr><td>≥10</td><td>(±1°)</td></tr><tr><td>>10>50</td><td>(±30′)</td></tr><tr><td>>50≥120</td><td>(±20′)</td></tr><tr><td>>120≥400</td><td>(±10′)</td></tr><tr><td>>400</td><td>(±5′)</td></tr></tbody></table></div>				尺寸(mm)	轴公差	孔公差	其余尺寸公差	≥0.5≥3	(-0.2,0)	(0,+0.2)	(-0.1,+0.1)	>3≥6	(-0.2,0)	(0,+0.2)	(-0.1,+0.1)	>6≥30	(-0.4,0)	(0,+0.4)	(-0.2,+0.2)	>30≥120	(-0.6,0)	(0,+0.6)	(-0.3,+0.3)	>120≥400	(-1,0)	(0,+1)	(-0.5,+0.5)	>400≥1000	(-1.6,0)	(0,+1.6)	(-0.8,+0.8)	>1000≥2000	(-2.4,0)	(0,+2.4)	(-1.2,+1.2)	>2000≥4000	(-4,0)	(0,+4)	(-2,+2)	>4000≥6000	(-6,0)	(0,+6)	(-3,+3)	>6000≥8000	(-10,0)	(0,+10)	(-5,+5)	>8000≥10000	(-16,0)	(0,+16)	(-8,+8)	尺寸(mm)	公差	≥0.5≥3	(±0.2)	>3≥6	(±0.5)	>6	(±1)	长度分段尺寸(mm)	公差	≥10	(±1°)	>10>50	(±30′)	>50≥120	(±20′)	>120≥400	(±10′)	>400	(±5′)	A													
尺寸(mm)	轴公差	孔公差	其余尺寸公差																																																																																			
≥0.5≥3	(-0.2,0)	(0,+0.2)	(-0.1,+0.1)																																																																																			
>3≥6	(-0.2,0)	(0,+0.2)	(-0.1,+0.1)																																																																																			
>6≥30	(-0.4,0)	(0,+0.4)	(-0.2,+0.2)																																																																																			
>30≥120	(-0.6,0)	(0,+0.6)	(-0.3,+0.3)																																																																																			
>120≥400	(-1,0)	(0,+1)	(-0.5,+0.5)																																																																																			
>400≥1000	(-1.6,0)	(0,+1.6)	(-0.8,+0.8)																																																																																			
>1000≥2000	(-2.4,0)	(0,+2.4)	(-1.2,+1.2)																																																																																			
>2000≥4000	(-4,0)	(0,+4)	(-2,+2)																																																																																			
>4000≥6000	(-6,0)	(0,+6)	(-3,+3)																																																																																			
>6000≥8000	(-10,0)	(0,+10)	(-5,+5)																																																																																			
>8000≥10000	(-16,0)	(0,+16)	(-8,+8)																																																																																			
尺寸(mm)	公差																																																																																					
≥0.5≥3	(±0.2)																																																																																					
>3≥6	(±0.5)																																																																																					
>6	(±1)																																																																																					
长度分段尺寸(mm)	公差																																																																																					
≥10	(±1°)																																																																																					
>10>50	(±30′)																																																																																					
>50≥120	(±20′)																																																																																					
>120≥400	(±10′)																																																																																					
>400	(±5′)																																																																																					
B					B																																																																																	
C					C																																																																																	
D	<div>1 展开长度L=958mm</div> <div>2 *尺寸供参考</div> <div>3 未指定的最大误差,见未注公差尺寸加工允许偏差表</div> <div>4 发蓝</div> <div>5 右向缠绕方向</div>				D																																																																																	
E					E																																																																																	
F	<table><tr><td>更改标记</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>处数</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>签字</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>日期</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>设计</td><td>李景彬</td><td>工艺</td><td>任伟</td><td colspan="3">弹簧</td><td>图幅</td><td>A4</td></tr><tr><td>校对</td><td>李冬梅</td><td>主管</td><td>陈超</td><td colspan="3"></td><td></td><td></td></tr><tr><td>标准</td><td>李冬梅</td><td>日期</td><td></td><td>重量</td><td>0.08</td><td>比例</td><td>1:15</td><td>共 1 页</td></tr><tr><td colspan="4"></td><td>材料</td><td colspan="3">65Mn</td><td>第 1 页</td></tr><tr><td colspan="4"></td><td>图号</td><td colspan="3">UD-6906</td><td>A</td></tr></table>				更改标记									处数									签字									日期									设计	李景彬	工艺	任伟	弹簧			图幅	A4	校对	李冬梅	主管	陈超						标准	李冬梅	日期		重量	0.08	比例	1:15	共 1 页					材料	65Mn			第 1 页					图号	UD-6906			A	F
更改标记																																																																																						
处数																																																																																						
签字																																																																																						
日期																																																																																						
设计	李景彬	工艺	任伟	弹簧			图幅	A4																																																																														
校对	李冬梅	主管	陈超																																																																																			
标准	李冬梅	日期		重量	0.08	比例	1:15	共 1 页																																																																														
				材料	65Mn			第 1 页																																																																														
				图号	UD-6906			A																																																																														
	1	2	3	4																																																																																		